

RF-405K TRACKER ONLY **\$159.00**



Key Features

- No radiation
- Frequency: 2.4GHz Digital RF
- 65,535 codes
- Operating temperature: 0 to 60 degree Celsius
- Humidity: 90%RH
- Detect distance: 500 meters

Model Name	405K		405K2	
Function	Search, Alarm with Vibration, 1 to 1		Search, Alarm with Vibration, 1 to 2	
Search Range	0~500m/1600ft		0~500m/1600ft	
Alarm Distance	Short Distance : 20~30m/65~98ft Long Distance : 50~60m/164~196ft		Short Distance : 20~30m/65~98ft Long Distance : 50~60m/164~196ft	
Master/Slave	Master (M05AM)x1	Slave (S4A)x1	Master (M05AM)x1	Slave (S04A)x2
Battery Type	LR44x2	CR2032x1	LR44x2	CR2032x2
Battery Life Time with Standby	30 days(8 hrs)	30 days(8 hrs)	20 days(8 hrs)	20 days(8 hrs)
Battery Life Time with Sleep	over 90 days	over 90 days	over 90 days	over 90 days
Beep Sound (at 10cm/3.9inch)	95 db	95 db	95 db	95 db
Vibration	Vibration Motor	None	Vibration Motor	None
Dimension (L/W/H)	52.8x39x13.2mm 2x1.6x0.52inch	Diam 45xW12mm Diam 1.77x0.47inch	52.8x39x13.2mm 2x1.6x0.52inch	Diam 45xW12mm Diam 1.77x0.47inch

PS. The connection range depends on the terrain environment because of radio wave efficiency.

To Order:

Email: Info@gpstracking4u.co.nz

Ph:0211446177

